



The image is purely indicative and may not fully reflect the configuration of the product.

## Micro Socket Connector 3P Screw L-N-PE D7-8 IP66/IP68/IP69

Code: **THB.381.B3E**



Any changes made to the data sheet may be made without prior notice.

## GENERAL INFORMATION

Installation Type	Socket and plug connection
Configuration	Grip
Locking mechanism	Push Pull
Color	Black (Plastic Components) - Techno Green (Rubber Components)
External Dimensions (mm)	Ø 14.0 x 53.0
External dimensions of plug-in socket inserted (mm)	Ø 14.0 x 90.0

## ELECTRICAL DATA

Connection points	1
Circuit Application	Power/Signal
Rated Current (AC/DC)	10Th
Rated Voltage (AC/DC)	500V AC
Additional-reinforced insulation (Class II)	250V
Impulse withstand voltage	4kV
Number of poles	3
Contact Symbology	L-N-E
Type of contacts	Screw
Thread/Tightening Torque	M2 - 0.1 Nm

## CONNECTION DATA

MIN flexible conductor cross-section without cable lug (mm <sup>2</sup> )	0.25
Flexible conductor cross-section MAX without cable lug (mm <sup>2</sup> )	1.00
Conductor sheathing length (mm)	10.00
Cable sheathing length (mm)	20.00
Recommended cable type	H05xxx/H07xxx
MIN Cable Diameter (mm)	7.00
Cable diameter MAX (mm)	8.00
Nut-gland tightening torque	1.5 Nm

## ENVIRONMENTAL CONDITIONS

IP Rating	IP66, IP68, IP69
	<i>*IP68 (30m/1h)</i>
Corrosion Resistance	Salt mist test : EN60068-2-11:2000
Connect-Disconnect Cycles	100 cycles
Temperature MIN/MAX (According to standard EN61984/EN60998)	-40°C/+125°C
Operating Temperature MAX	+60°C
Tracking Index	PTI 175

## MATERIALS

Connector	PA66 GF UL94 V0
Cable gland	PA66 GF UL94 V2
Seals	TPE
Cable grommets	TPE
Overvoltage Category	II
Degree of pollution	2
Property	Halogen Free - Silicone Free
Contacts	Brass
Contact Screws	Steel

## PRODUCT COMPLIANCE

IEC Approved	EN 61984:2009
--------------	---------------

## COMMERCIAL DATA


EAN	8057457095921
Product Configuration	Industrial Packaging (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Weight/piece (gr)	7.80
Box size (mm)	200 x 200 x 120
Customs Code	85369010
Country of origin	ITALY

## CERTIFICATIONS

Effettua la login per vedere questa sezione.

## TECHNICAL DOCUMENTATION

### Technical Documentation:

File	Format	Dimension
 606002032_TH381.pdf	PDF	571.88 KB

## 2D DRAWINGS

### 2D Drawings:

File	Format	Dimension
 THB.381.B3E.pdf	PDF	390.20 KB

## 3D FILES

Effettua la login per vedere questa sezione.

## COMMUNICATION MATERIAL

Effettua la login per vedere questa sezione.